



P R O D U C T I N F O R M A T I O N

Passenger Car and Light Commercial Vehicle Oils Gulf Formula GVX

Product Description:

Gulf Formula GVX 5W-30 is the latest low emission synthetic engine oil with fuel economy credentials exclusively developed to meet the requirements of the entire range of passenger cars of Volkswagen. Formulated from carefully selected synthetic base oils and advanced additive technology meeting mid SAPS (Sulphated ash, Phosphorous & Sulphur) requirements so as to be fully compatible with the most modern Diesel Particulate Filters (DPFs) and Gasoline Catalytic Converters. **Gulf Formula GVX 5W-30** helps in prolonging the life and maintaining the efficiency of after exhaust treatment devices used in the latest generation gasoline and diesel cars. **Gulf Formula GVX 5W-30** has been designed to deliver outstanding performance in conjunction with fuel economy for extended drain intervals.

Features/Benefits:

Gulf Formula GVX 5W-30 low Ash content reduces particulate build-up in DPFs and helps in extending the regeneration intervals. The mid SAPS technology reduces poisoning and degradation of catalysts and prolongs life of after treatment devices and outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended oil life. Exceptional low temperature fluidity aids cold start and protects against wear at start-up and excellent antiwear property protects against engine wear and facilitates extended engine life. Enhanced frictional properties result in long-lasting fuel economy.

Recommended Applications:

Gulf Formula GVX 5W-30 is recommended for all gasoline and diesel powered passenger car engines of Volkswagen including the latest vehicles meeting Euro 4 emission norms requiring the most advanced VW 504 00/ 507 00 quality oils for long life service. **Gulf Formula GVX 5W-30** is strongly recommended for the latest generation high performance gasoline and diesel engines in passenger cars and vans, equipped with exhaust treatment devices such as particulate filters, catalytic converters, exhaust gas re-circulation (EGR) etc requiring ACEA A3/B4 & ACEA C3 quality oils.

Gulf Formula GVX	SAE 5W-30	Product Code: 1205
Specifications:		
Meets: ACEA A3/B4, C3 Approved by: VW 504.00/507.00		
Typical Properties:		
Density @ 15°C, kg/m ³		851
Viscosity @ 100°C, mm ² /s		11.9
Flash Point, °C		200
Pour Point, °C		-39