



P R O D U C T I N F O R M A T I O N

Passenger Car and Light Commercial Vehicle Oils Gulf Formula G

Product Description:

Gulf Formula G 5W-40 is a supreme performance passenger car motor oil formulated from finest quality synthetic base stocks and state-of-the-art additive technology. **Gulf Formula G 5W-40** has been specially developed for all modern turbocharged, high output gasoline and diesel engines of passenger cars, SUVs, light vans and trucks. **Gulf Formula G 5W-40** has been designed to deliver long service life and minimizes deposits in engine and turbocharger to ensure rated engine power and torque. **Gulf Formula G 5W-40** oils are designed to exceed the latest industry specifications and the major car manufacturers' service fill requirements.

Features/Benefits:

Gulf Formula G 5W-40 has outstanding thermo-oxidative stability that reduces deposits & sludge build-up and facilitates extended oil & engine life, and improved fuel economy and extended drain intervals reduce the cost of ownership, excellent low temperature fluidity aids quick cold start and provides wear protection at start-up. Outstanding Stay-in-Grade performance ensures reliable lubrication even at higher load and operating temperatures and superior antiwear technology provides excellent wear protection under all conditions, active cleaning agents ensure maximum engine cleanliness.

Recommended Applications:

Recommended for all modern vehicles including high performance, turbo-charged, multi valve, direct injection gasoline and diesel engines of passenger cars. **Gulf Formula G 5W-40** exceeds the requirements of most modern European, North American and Japanese passenger cars including gasoline powered racing cars.

| | | |
|---------------------------------------------------------------------------|------------------|---------------------------|
| Gulf Formula G | SAE 5W-40 | Product Code: 1210 |
| Specifications: | | |
| Meets: ACEA A3/B4 Approved by: API SM/CF, MB 229.3 en VW 502.00/505.00 | | |
| Typical Properties: | | |
| Density @ 15°C, kg/m ³ | | 859 |
| Viscosity @ 100°C, mm ² /s | | 14.1 |
| Flash Point, °C | | 200 |
| Pour Point, °C | | -42 |