



PRODUCT INFORMATION

Hydraulic Oils

Gulf Harmony Synth

Product Description:

Gulf Harmony Synth oils are extra high quality fully synthetic hydraulic fluids, formulated for wide temperature range applications and severe duty conditions. Blended with PolyAlphaOlefins and selected additives they provide properties far exceeding those obtainable with conventional premium hydraulic fluids, and are ideally suited for wide temperature range conditions (-45°C to +80°C). These properties are providing maximum life-time of hydraulic components. **Gulf Harmony Synth** is best suited in most of the pumps used in industry, automobiles, and in machinery for agriculture, road construction and hydraulic engineering.

Features/Benefits:

Gulf Harmony Synth oils have excellent thermal and oxidation stability, anti-wear properties and long life time of the components in the system. Very good protection against rust and corrosion excellent demulsification capacity and is very fluid at extreme low temperatures (no pre-heaters necessary).

Applications:

Gulf Harmony Synth is suitable for all hydraulic systems.

Gulf Harmony Synth	
MEETS THE FOLLOWING SPECIFICATIONS:	
ISO 15380 HEPR	Denison HF-0, HF-1, HF-2
DIN 51524/2 HLP	Cincinnati Lamb, P-86/P-69/P-70
AFNOR NFE 48-603 HM	US Steel 127

Gulf Harmony Synth ISO VG	32	46	68
Product Code	3696	3697	3698
Density @ 15°C, kg/m ³	871	872	875
Viscosity @ 40°C, mm ² /s	32	46	68
Flash Point, °C	192	195	198
Pour Point, °C	-54	-45	-42