



## Greases

### Gulflex EPG 2

#### *Product Description:*

**Gulflex EPG 2** is a lithium thickened lubricating grease based on mineral oil. **Gulflex EPG 2** contains antioxidants, corrosion inhibitors, EP/AW additives and 3 % solids. **Gulflex EPG 2** is a typical multi-purpose “moly” grease which can be used in various applications within given temperature limits. The lubricating grease offers good stability, load carrying capacity and corrosion protection, making it suitable for heavily loaded slow moving bearings as well as wet environments. **Gulflex EPG 2** has high load carrying capacity and good corrosion protection.

#### *Application:*

**Gulflex EPG 2** is a high quality multipurpose “moly” grease that can be used in both industrial and automotive applications. The combination of molybdenum disulphide and graphite gives extra protection in applications with slow moving or oscillating bearings. Lubricating greases with solids are not suitable for rolling bearings at high speed.

Gulflex EPG 2	
Consistency, ASTM D217	NLGI 2
Product Code	5020
<b>SPECIFICATIONS:</b>	
ISO 6743-9	L-XCCIB 2
DIN 51 502	KPF2K-30
<b>PROPERTIES:</b>	
Colour	Black
Dropping Point, °C	>180
Viscosity base oil @ 40°C/100°C, mm <sup>2</sup> /s	110/12
Penetration 60 strokes, ISO 2137, mm/10	265-295
Temperature range continuous operation, °C	-30 tot +120