



Greases

Gulf Crown LC 2

Product Description:

Gulf Crown LC 2 is a lithium complex thickened lubricating grease based on mineral oil. The grease contains antioxidants, corrosion inhibitors and EP/AW additives. The lithium complex soap makes **Gulf Crown LC 2** suitable for applications within a very wide temperature range and especially applications at elevated temperatures. The complex soap structure also gives **Gulf Crown LC 2** a high degree of mechanical stability. This enhances the performance in vibrating housings and prolongs re-lubrications intervals. **Gulf Crown LC 2** is excellent at high temperatures, has very good mechanical stability, high load carrying capacity and good corrosion protection.

Application:

Gulf Crown LC 2 is suited for both industrial and automotive applications. The product's all round properties make it the primary choice for various types of bearing applications including heavy load conditions and temperature peaks up to 220°C. **Gulf Crown LC 2** meets Volvo standard "Lubricating grease 97720".

Gulf Crown LC 2	
Consistency, ASTM D217	NLGI 2
Product Code	5023
SPECIFICATIONS:	
ISO 6743-9	L-XCDIB2
DIN 51 502	KP2N-30
PROPERTIES:	
Colour	Light yellow
Dropping Point, °C	>260
Viscosity base oil @ 40°C/100°C, mm ² /s	210/18
Penetration 60 strokes, ISO 2137, mm/10	265-295
Temperature range continuous operation, °C	-30 tot +140