



Engine Coolants (Ready to Use)

Gulf Coolant LL

Product Description:

Gulf Coolant LL is a silicate-holding coolant composed of mono-ethylene glycol under addition of a wide range of additives. **Gulf Coolant LL** is a top quality coolant, which belongs to the latest generation silicate-holding coolants. **Gulf Coolant LL** can be used throughout the year in cooling systems in all petrol and diesel engines. Thanks to the unique and well balanced additives package and high quality mono-ethylene glycol, **Gulf Coolant LL** belongs to the highest quality in the market. **Gulf Coolant LL** needs to be used undiluted to give a protection to -38°C.

Features/Benefits:

- * Nitrite, Amine and Phosphate-free.
- * A good protection of all metals in the cooling system and engine.
- * Neutral in relation to gaskets and hoses.
- * Strong resistance against foam.

Warning : **Keep all antifreezes out of reach of children!!! Do not drink antifreeze!!!
If swallowed, induce vomiting and immediately call a doctor!!!**

Gulf Coolant LL (Ready to use)	
PRODUCT CODE	6938
SPECIFICATIONS:	
BRITISH STANDARD BS 6580	MB 325.2
AFNOR 15-601	GM/OPEL
ASTM D3306	DEUTZ/MWM
SAE J 1034	BMW
CUNA NC 956-16	VW TL 774C/G11

TYPICAL PROPERTIES:	
DENSITY @ 15°C, kg/m ³	1078
pH	7.6-8.5
CRISTALLISATION POINT	-38°C
COLOUR	Blue