



PRODUCT INFORMATION

Gas Engine Oils

Gulfc0 LA 40

Product Description:

Gulfc0 LA 40 is a low ash natural gas engine oil. **Gulfc0 LA 40** oil is blended with high quality base oils and a balanced additive package that provides detergency, dispersancy, resistance to oxidation and bearing corrosion and low temperature deposit control. These detergents and dispersants effectively reduce sludge and varnish and helps to keep the engine components clean. **Gulfc0 LA 40** is suitable for high power engines, with or without turbo charger, such as Caterpillar. **Gulfc0 LA 40** is also suitable for the lubrication of crankcases of gas compressors, driven by gas engines.

Features/Benefits:

Gulfc0 LA 40 has exceptional deposit, wear, oil oxidation and oil nitration control, meets catalyst manufacturers performance, has very good detergent and dispersant properties and good resistance against formation of foam and corrosion.

Gulfc0 LA 40	
Performance Specifications: API CF	
Product Code: 1894	
Typical Properties:	
SAE VG	40
Density at 15°C, kg/m ³	896
Viscosity at 40°C, mm ² /s	142
Viscosity at 100°C, mm ² /s	14.5
Viscosity Index	>95
Flash Point, °C	240
Pour Point, °C	-15
TBN, mgKOH/g	4.9
Sulphated Ash Content, % wt	0.45